



## Machine features:

1. The edge banding machine is made of selected high-hardness steel, which is durable and increases the service life of the machine.
2. The edge banding machine integrates the switch operation buttons, which can be operated in all aspects and functions to simplify the workflow.
3. The edge banding machine is used for edge sealing of various decorative materials, and can be used for film sealing and packaging of various wood boards, PVC boards, plastic boards and other boards.

The automatic side sealing machine is suitable for batch film sealing and cutting packaging of long and wide products in industries such as door panels, photo frames, picture frames, floors, tiles, wooden products, hardware and plastics, and can be used in conjunction with PE film heat shrink packaging machines.

## Parameters:

Automatic side sealing cutting and shrinking machine		
Machine model	SPR-50	SPR-5030LW
Power Supply	380V/50-60Hz	380V/50-60Hz
power	2kw	16kw
Product packaging size	W+H≤450mm/H<150	L1200xW400*H200m m
Dimensions of sealing knife/Shrink tunnel	W:500mm	L1500*W500xH300m m
Packaging speed	20-40pcs/min	20-60pcs/min
Use gas source	6-8kg/cm <sup>3</sup>	6-8kg/cm <sup>3</sup>
maximum current	10A	26A
net weight	700kg	300kg
Mechanical dimension	L1800*W1000*H1536m m	L1800*W1100*H1250 mm
<p><b>(Note: the equipment size is standard edge sealing model, and the model can be customized according to the specific product size.)</b></p>		



## Machine features:

1. Automatic feeding, the length is automatically adjusted by the combination of electric eye and timer. Equipped with induction motor, automatic winding of waste film.
2. The sealing and cutting knife adopts Teflon coating, which is not easy to stick to the film, high temperature resistant and crack-proof. The sealing frame adopts alloy steel, and the frame is not easy to deform.
3. Imported servo motor, precise and fast positioning; strong power, long service life and durable.

This machine has the characteristics of photoelectric automatic detection of products, motor frequency conversion speed regulation, constant temperature heating of sealing knife, and servo sealing and cutting. It is very suitable for sealing and cutting of POF film. Widely used in large-volume shrink packaging in software, food, cosmetics, printing, pharmaceuticals, beverages, hardware and other industries.

## Parameters:

Automatic servo motor side sealing, cutting and shrinking machine		
Machine model	SPR-50H	SPR-5030LW
Power Supply	3&380V 50-60HZ	380V/50-60Hz
power	3KW	16kw
Product packaging size	W+H<450mm/H<170mm	L1200xW400*H200mm
Dimensions of sealing knife	W:500mm	L1500*W500xH300mm
Packaging speed	30-50pcs/min	20-60pcs/min
Use gas source	6-8kg/cm3	6-8kg/cm3
maximum current	10A	26A
net weight	800kg	300kg
Mechanical dimension	L2100mmxW1700mmxH1350mm	L1800*W1100*H1250mm
<b>(Note: the size of the equipment is standard machine, and the machine can be customized according to the specific product size.)</b>		